

260012

REPLACEMENT PARTS LIST					
ITEM	PART NO.	DESCRIPTION			
1	260143	ROLLER CARRIER ASSEMBLY	1		
2	051159	JACK ASSEMBLY (54")			
3	052722	SEAL KIT			
4	108501	ROLLER: PLATFORM			
5	050769	LIFT CHAIN ASSEMBLY			
6	260072	KIT: WHEEL LOCK "HANDLE STYLE" (PL-40 PRE-10/1996)			
	260080	0080 KIT: WHEEL LOCK "FOOT STYLE" (PL-40/54)			
7	052868	WHEEL: "H1" 8 X 2 MOR/AC	2		
8	108303	CASTER: SWIVEL 3-1/2X1-1/4" (DPL)	2		
9	051813	KIT: PLATFORM ROLLER W/ HARDWARE	4		

STEEL FRAME PEDALIFTS

- Wheel locks are standard on all models.
- Frame and lift heights vary among models.
- Adjustable fork widths from 6.5" to 21.75"
- Adjustable fork widths outer dimensions are 6-1/2" to 21-3/4" wide

Four Wheeled Hydraulic Models

- Foot operated hydraulic pump raises platform, foot rélease lowers platform.
- Platform sit 5.75" above the floor.
- Wheel lock standard.

P/N 260012

Model: DPL-54-F

Lift Height: 54"

18"D X 3"W Fork: Weight: 172 lb. Capacity: 750 lb. O.A.H

60.5" High

22.5" Wide O.A.W

	THS DRAWNO	IN ALL PARTICULARS IS WESCO MFGR.	CO. PROPERTY. ALL RIGHTS OF D	ESIGN, INVENTION OR USE OF ARE RESERVED.
PRINT ISSUED	ad a state of the		MANUFACT	
ILLKIINI 1990EDI		NORTH WAI	.ES	PENNA. 19454
		PART NAME	ME DPL-54-F (PEDA-LIFT)	DRAWN:
JUN 04 2002		NOISE DPL-54-F		CHECKED:
	[a]	TOLERANCE UNLESS (THERWISE SPECIFIED	APP. ENGR.
WESCO MANUFACTURING		FRACTION 3 PLACE DEC	MAL 2 PLACE DECIMAL	SCALE:
		± 1/64 ± .005		0
ENGINEERING DEPARTMENT		ANGULAR ± 1-1/2° BREAK ALL SHARP EDGES	SHEET 1 OF 1 AND REMOVE ALL BURRS	C-260012 [ଛୁ