



Foot and Powered Portable Hydraulic Lift Table

- AC and DC power option available.
- 0.25" reinforced steel top and base.
- 2 rigid and 2 swivel steel wheel casters.
- Standard designs available in 2 sizes: 30" x 30" and 48" x 30"
- Available in 4 capacities: 3,000 4,000 5,000 and 6,000.
- Precision telescoping guide tubes.

Specs

- Capacity: 6000 lbs
- Table size: 30" x 30"
- Raised height: 44"
- Lowered height: 26"
- Caster: 6"
- Lift: 18"
- Weight(foot opp.): 454 lbs
- Weight(electric opp.): 505 lbs

THIS DRAWING IN ALL PARTICULARS IS WESCO INDUSTRIAL PRODUCTS INC. PROPERTY. ALL RIGHTS OF DESIGN, INVENTION OR USE OF ARE RESERVED.

REV.	ECN & DATE	APP	WESCO INDUSTRIAL PRODUCTS INC.							
			LANSDALE PENNA. 19446							
			PART NAME HT-3036-18		DRAWN:					
			TOLERANCE UNLESS OTHERWISE SPECIFIED		CHECKED:					
			FRACTION 3 PLACE DECIMAL 2 PLACE DECIMAL		APP. ENGR.					
			<table border="1" style="width: 100%;"> <tr> <td>± 1/64</td> <td>± .005</td> <td>± .01</td> </tr> <tr> <td colspan="2">ANGULAR ± 1-1/2'</td> <td>SHEET 1 OF 1</td> </tr> </table>		± 1/64	± .005	± .01	ANGULAR ± 1-1/2'		SHEET 1 OF 1
± 1/64	± .005	± .01								
ANGULAR ± 1-1/2'		SHEET 1 OF 1								
			SCALE: B- 496060							
			BREAK ALL SHARP EDGES AND REMOVE ALL BURRS							