



Foot and Powered Portable Hydraulic Lift Table

- AC and DC power option available.
- 0.25" reinforced steel top and base.
- 2 rigid and 2 swivel steel wheel casters.
- Standard designs available in 2 sizes: 30" x 30" and 48" x 30"
- Available in 4 capacities: 3,000 4,000 5,000 and 6,000.
- Precision telescoping guide tubes.

Specs

- Capacity: 6000 lbs
- Table size: 48" x 30"
- Raised height: 48"
- Lowered height: 28"
- Caster: 6"
- Lift: 20"
- Weight(foot opp.): 589 lbs
- Weight(electric opp.): 640 lbs

THIS DRAWING IN ALL PARTICULARS IS WESCO INDUSTRIAL PRODUCTS INC. PROPERTY. ALL RIGHTS OF DESIGN, INVENTION OR USE OF ARE RESERVED.

| | | | | | | | | | | | | | |
|--|------------|--------------|--|--|------------|--------|-------|------------------|--|--------------|--|--|--|
| REV. | ECN & DATE | APP | WESCO INDUSTRIAL PRODUCTS INC. | | | | | | | | | | |
| | | | LANSDALE PENNA. 19446 | | | | | | | | | | |
| | | | PART NAME HT-3046-20 | | DRAWN: | | | | | | | | |
| | | | TOLERANCE UNLESS OTHERWISE SPECIFIED | | CHECKED: | | | | | | | | |
| | | | FRACTION 3 PLACE DECIMAL 2 PLACE DECIMAL | | APP. ENGR. | | | | | | | | |
| | | | <table border="1" style="width: 100%;"> <tr> <td>± 1/64</td> <td>± .005</td> <td>± .01</td> </tr> <tr> <td colspan="2">ANGULAR ± 1-1/2'</td> <td>SHEET 1 OF 1</td> </tr> <tr> <td colspan="3" style="text-align: center;">BREAK ALL SHARP EDGES AND REMOVE ALL BURRS</td> </tr> </table> | | ± 1/64 | ± .005 | ± .01 | ANGULAR ± 1-1/2' | | SHEET 1 OF 1 | BREAK ALL SHARP EDGES AND REMOVE ALL BURRS | | |
| ± 1/64 | ± .005 | ± .01 | | | | | | | | | | | |
| ANGULAR ± 1-1/2' | | SHEET 1 OF 1 | | | | | | | | | | | |
| BREAK ALL SHARP EDGES AND REMOVE ALL BURRS | | | | | | | | | | | | | |
| | | | SCALE: | | | | | | | | | | |
| | | | B- 496079 | | | | | | | | | | |
| | | | REV | | | | | | | | | | |